# Impact Wrenches (CP) Sanders & Blue Tork (CP) Air Ratchets (CP) **Buffers & Grinders (CP)** Air Drills (CP) Air Tools & Accessories (RPG) Impact Wrenches (IR) Cordless Tools (IR) Cordless Tools (Milwaukee) Hammers, Grinders & Drills (IR) **Air Tool Lubricants & Conditioners**

Accessories & Work Stations

A R TOOLS



41



# **Impact Wrenches**

#### 3/8" HEAVY DUTY AIR IMPACT WRENCH

One hand push button forward/reverse power regulator
Handle exhaust directs air away from the work area • 360° air inlet swivel prevents hose kinks • APPLICATIONS: general repair, transmission work, exhaust systems and body shops • ULTIMATE TORQUE: 200 ft./lb.

ASCOT NO. 152-00724 DESCRIPTION 3/8" Heavy Duty Air Impact Wrench

#### 3/8" SUPER DUTY ANGLE IMPACT WRENCH

MFG. NO.

CP724H

High Durability • Compact • Powerful
 Comfort • Great Control • Easy
 operation • Single handed forward/

operation • Single handed forward/ reverse operation • 3 positions in forward and 1 in reverse • 185 ft./lb. (250 Nm) of maximum torque in reverse

DURABLE & HEAVY DUTY



ASCOT NO. MFG. NO 152-07727 CP7727 DESCRIPTION 3/8" Super Duty Angle Impact Wrench

#### 1/2" SUPER DUTY ANGLE IMPACT WRENCH

- High durability Compact Powerful
- Comfort Great control Easy operation
- Single handed forward/reverse operation
- 3 positions in forward and 1 in reverse
- 220 ft./lb. (300 Nm) of maximum

torque in reverse

ASCOT NO. MFG. NO. 153-07737 CP7737

. DESCRIPTION 1/2" Super Duty Angle Impact Wrench



C.

c.

153-07737

152-07727

#### 3/8" HEAVY DUTY AIR IMPACT WRENCH

• The most powerful 3/8" of its

class for general maintenance • Maximize operator comfort with an extremely light and well balanced design • Most convenient and unique reverse technology in the market • ULTIMATE TORQUE: 415 ft./lb.

| ASCOT NO. | MFG. NO. |  |
|-----------|----------|--|
| 152-07729 | CP7729   |  |
|           |          |  |

DESCRIPTION 3/8" Heavy Duty Air Impact Wrench

#### 1/2" SUPER DUTY AIR IMPACT WRENCH

• Tackle the tough jobs with the power and speed of this true workhorse • Patented clutch provides smooth operation and extreme durability • One hand push button forward reverse

power regulator • 4 positive power settings in forward and ultimate power in reverse • Compact design with comfortable contoured handle • ULTIMATE TORQUE: 610 ft./lb.

| ASCOT NO. | MFG. NO. | DESCRIPTION        | 153-17492 |
|-----------|----------|--------------------|-----------|
| 153-07492 | CP749    | 1/2″ Impact Wrench |           |
| 153-17492 | CP749-2  | 2" Extended Anvil  |           |

#### 1/2" HEAVY DUTY AIR IMPACT WRENCH

 One hand push button forward/reverse power regulator • 4 positive power setting
 Ultimate power in reverse • Differential regulator allows the operator to match the required power to the job • Patented oil bath Dyna-Pact clutch delivers smooth operation and extended durability • Handle exhaust with 360° air inlet swivel to prevent kinks • Power and economy for general repair, transmission work, exhaust systems and body shops
 ULTIMATE TORQUE: 425 ft./lb.

| ASCOT NO. | MFG. NO. | DESCRIPTION 153-01734   |
|-----------|----------|---|
| 153-00734 | CP734H   | 1/2" Impact Wrench  |
| 153-01734 | СР734НК  | KIT INCLUDES: CP734H, (1) Set of 5 SAE<br>Sockets: 1/2", 5/8", 3/4", 7/8", 15/16" |



153-00734

1/492

Classic

Classia



#### 1/2" SUPER DUTY AIR IMPACT WRENCH-TIRE TOOL

 Patented spring hammer clutch for smooth operation and extended durability • Low air consumption and high torque make this tool very efficient • ULTIMATE TORQUE: 665 ft./ lb. • Comfort and control with new ergonomic grip and trigger • SUITED FOR ALL MAINTENANCE APPLICATIONS: Light vehicle tire changing operations, light vehicle mechanical repair, MRO applications



| ASCOT NO. | MFG. NO. | DESCRIPTION                                   |
|-----------|----------|---|
| 153-00736 | CP7736   | 1/2" Super Duty Air Impact Wrench - Tire Tool |
| 153-07336 | CP7736-2 | 2" Extended Anvil                             |

#### 1/2" DRIVE STUBBY IMPACT WRENCH



The 1/2" Drive Stubby Impact Wrench in use.

MFG. NO.

CP7732

ASCOT NO. 153-07732 DESCRIPTION 1/2" Drive Stubby Impact Wrench





153-07732

#### 1/2" SUPER DUTY AIR IMPACT WRENCH-TIRE TOOL

960 ft./lb. of torque (1,300 Nm) • Hard anodized end plates • Hard chromium aluminum cylinder • Twin hammer mechanism
Lightweight due to the Composite motor housing • COMPACT: Only 6.6" long
Curved handle with rubber

material resistant to most chemicals used in workshops • Full teasing trigger • 360° swivel air inlet • Friction ring socket retainer

153-77482

153-077748



The 1/2" Super Duty Air Impact Wrench-Tire Tool in use.

| ASCOT NO. | MFG. NO. | DESCRIPTION                                 |
|-----------|----------|---|
| 153-07748 | CP7748   | 1/2" Super Duty Air Impact Wrench-Tire Tool |
| 153-77482 | CP7748-2 | 2" Extended Anvil                           |

#### 1/2" HEAVY DUTY AIR IMPACT WRENCH

 Side-To-Side (S2S) forward/reverse functionality • Perfectly balanced to reduce strain on wrist and forearm • Twin hammer mechanism • ULTIMATE TORQUE: 955 ft./lb

| PERFECT<br>BALANCE |          | FEATURES<br>S2S (SIDE-<br>TO-SIDE) | 153-77492 |
|--------------------|----------|------------------------------------|-----------|
| ASCOT NO.          | MFG. NO. | DESCRIPTION                        |           |
| 153-07749          | CP7749   | 1/2" Impact Wrench                 |           |
| 153-77492          | CP7749-2 | 2" Extended Anvil                  |           |



### Impact Wrenches (cont.)

#### 3/4" HEAVY DUTY AIR IMPACT WRENCH

• Smoothest operating 3/4" impact on the market • One hand push button forward/reverse power regulator • Handle exhaust with 360° air inlet swivel • APPLICATIONS: spring work, truck and bus maintenance, farm machines & construction equipment • ULTIMATE TORQUE: 1,000 ft./lb.



#### 3/4" HEAVY DUTY AIR IMPACT WRENCH

 Reduced Length at only 7.9" • All controls within reach • Variable speed trigger • One-hand power adjustment • One-hand reverse system • 1440 ft./lb. (1950 Nm) of maximum torque • Composite motor housing • Twin

hammer mechanism • 360° swivel air inlet Socket retainer ring combined with hole retainer ASCOT NO. DESCRIPTION MFG. NO. 154-07769 CP7769 3/4" Impact Wrench 154-77696 CP7769-6 6" Extended Anvil

#### 3/4" SUPER DUTY AIR IMPACT WRENCH - "D" HANDLE

• LIGHTWEIGHT: 3/4" at only 14.3 lb. • 1300 ft./lb. (1760 Nm maximum torque in reverse) • Twin hammer mechanism • Steel motor • Intuitive Forward/Reverse lever & power regulator on both sides • 4-position power settings on both sides • Side handle with soft-touch grip • Down exhaust • Aluminum housing • Composite cover on the



| ASCOT NO. | MFG. NO.  | DESCRIPTION       |
|-----------|-----------|-------------------|
| 154-27763 | CP7763D   | 1″ Short Shank    |
| 154-37763 | CP7763D-6 | 6" Extended Anvil |

1" HEAVY DUTY AIR IMPACT WRENCH

 Chicago Pneumatic's strongest and most powerful 1" Impact Wrench • Operator productivity • Convenient reverse valve • Ideal for high volume tire work on trucks, buses, and heavy equipment • 1" impact wrench with 7" extended anvil Rocking dog clutch • 4-position power settings throttle for ease of use



ASCOT NO MFG. NO. 155-50000 CP5000

DESCRIPTION 7" Extended Anvil

#### 1" SUPER DUTY AIR IMPACT WRENCH

• 14.5 lb. (6.6 kg) • Twin hammer mechanism • Steel motor • Intuitive forward/ reverse lever & power regulator on both sides • 4-position power settings on both sides • Side handle with soft touch grip • Down exhaust • Aluminum housing • Composite cover on the clutch housing • Socket retainer ring • 1300 ft./lb. (1760 Nm) maximum torque in reverse



| ASCOT NO. | MFG. NO.  | DESCRIPTION       |
|-----------|-----------|-------------------|
| 155-07773 | CP7773D   | 1" Short Shank    |
| 155-77736 | CP7773D-6 | 6" Extended Anvil |

#### 1" HEAVY DUTY AIR IMPACT WRENCH

 High performance clutch provides longer life under tough conditions High-efficiency 6 vane motor for maximum performance • Bottom exhaust directs exhaust away from the operator • Three-position power regulator with directional control • ULTIMATE TORQUE: 1,620 ft./lb.



| 155-07778 | CP7778     | 1" Short Shank                   |
|-----------|------------|----------------------------------|
| 155-77786 | CP7778-6   | 6" Extended Anvil                |
| 155-27786 | CP7778SP-6 | #5 Spline with 6" Extended Anvil |







### 1" Heavy Duty Air Impact Wrench

- 2140 ft./lb. (2900 Nm) of maximum torque in reverse
- Pinless closed reinforced rocking dog impact mechanism .
- Socket retainer ring combined with hole retainer
- Ergonomic side handle
- Full teasing trigger
- Regulator with integrated forward/reverse with 3-position power settings in both directions

| ASCOT NO. | MFG. NO.   | DESCRIPTION                      |  |
|-----------|------------|----------------------------------|--|
| 155-07782 | CP7782     | 1" Short Anvil                   |  |
| 155-77826 | CP7782-6   | 6" Extended Anvil                |  |
| 155-17782 | CP7782-SP6 | #5 Spline with 6" Extended Anvil |  |
|           |            |                                  |  |

155-77826

#### 1" HEAVY DUTY AIR IMPACT WRENCH

• High Operator Comfort-Ergonomic D-Handle with full teasing trigger • HIGH DURABILITY: Pinless closed reinforced rocking dog mechanism in oil bath SHOCK ABSORBING: Rubber bumper protecting both applications and tool (included) • POWERFUL AND LIGHT: 1770 ft./lb. (2400 Nm) in reverse



| ASCOT NO. | MFG. NO. | DESCRIPTION       |
|-----------|----------|-------------------|
| 155-07783 | CP7783   | 1" Short Shank    |
| 155-77836 | CP7783-6 | 6" Extended Anvil |



• LIGHTWEIGHT: Only 6.9 lb. (3.15 kg) thanks to a composite motor housing for an improved

operator comfort • Socket retainer ring combined with hole retainer • Twin hammer mechanism • ALL CONTROLS WITHIN REACH: Variable speed trigger, One-hand power adjustment, One-hand reverse system • 360° swivel air inlet • 1440 ft./lb. (1950 Nm in reverse)

| ASCOT NO. | MFG. NO. | DESCRIPTION       | 155-07779 |  |
|-----------|----------|-------------------|-----------|--|
| 155-07779 | CP7779   | 1" Impact Wrench  |           |  |
| 155-17779 | CP7779-6 | 6" Extended Anvil |           |  |
|           |          |                   |           |  |

#### 1" SUPER DUTY AIR **IMPACT WRENCH**

· Rocking dog clutch for smooth operation

and extreme durability

155-07976

Classi

• Teasing throttle for easy bolt starting Convenient reverse valve for easy directional changes 
 Choice of professional mechanics for high volume tire work on trucks, buses and heavy equipment • ULTIMATE TORQUE: 1,400 ft./lb.

| ASCOT NO. | MFG. NO.  | DESCRIPTION                     |
|-----------|-----------|---------------------------------|
| 155-07971 | CP797     | 1" Short Shank                  |
| 155-07976 | CP797-6   | 6" Extended Shank               |
| 156-79716 | CP797SP-6 | 6" Extended Shank and #5 Spline |
|           |           |                                 |





# Sanders & Blue Tork

#### HEAVY DUTY HIGH-SPEED SANDER

• Built-in regulator and variable speed throttle for precise speed control • Rugged, energy efficient 1/2 HP motor • APPLICATIONS: Ideal for small jobs or hard to reach spots including paint removal, shaping filler patches, smoothing and rust removal • FREE SPEED: 14,000 RPM



#### MINI DISC SANDER KIT

• KIT INCLUDES: CP7202 Mini Disc Sander plus (1) 3" backing pad, (10) 3" 80, 100 & 120 grit sanding discs, (1) 3" fine, medium and coarse surface prep disc & a spindle wrench packed in a heavy duty carrying case • FREE SPEED: 15,000 RPM



158-07202

ASCOT NO. MFG. NO. CP9778 158-00778

DESCRIPTION

Heavy Duty High-Speed Sander

ASCOT NO. MFG. NO. CP7202D 158-07202

DESCRIPTION Mini Disc Sander Kit



### 1" Non-Impact Wrench (Blue Tork)

- Two pneumatic motors for rundown and final tightening
- Preset and adjustable shut off for torque control
- QUALITY: Precise, accurate tightening • to the manufacturer's recommended torgue and angle specifications
- ENVIRONMENT IMPROVEMENTS: by increasing durability of the tools, we reduce waste
- ERGONOMICS: very low noise level, virtually no vibration

- EFFICIENCY: Precise and accurate tightening, less fatigued operators
- MAXIMUM TORQUE: 660 ft./lb.

| ASCOT NO. | MFG. NO.     | DESCRIPTION                         |
|-----------|--------------|-------------------------------------|
| 168-07600 | CP7600xB     | Non-Reversible Single Torque Preset |
| 168-07602 | CP7600xB-R   | Reversible Single Torque Preset     |
| 168-07603 | CP7600xB-R4P | Reversible 4 Torque Preset Selector |





# Air Ratchets

#### QUICK REFERENCE CHART

| CP No.  | Ascot No. | Sq. Drive<br>(mm) | Std Bolt Size<br>(mm) | Net Wt. (kg) | Avg Air Cons.<br>(CFM) | Air Inlet (in.) | Min. Hose Size<br>(in.) | Working Torque<br>(ft./lbs.) | Max Torque (ft./lbs.) |
|---------|-----------|-------------------|-----------------------|--------------|------------------------|-----------------|-------------------------|------------------------------|-----------------------|
| CP826   | 151-00826 | 1/4" (6)          | 1/4" (6)              | 1.13 (0.51)  | 3.5                    | 1/4"            | 3/8" (10)               | 5-15 (7-20)                  | 15 (20)               |
| CP828   | 151-00828 | 3/8" (10)         | 3/8" (10)             | 2-5/8 (1.2)  | 4                      | 1/4"            | 3/8" (10)               | 10-50 (14-68)                | 50 (68) 150 RPM       |
| CP7829  | 152-07829 | 3/8" (10)         | 3/8" (10)             | 1.235 (2.72) | 4                      | 1/4″            | 3/8" (10)               | 10-55 (15-68)                | 95 (70)               |
| CP7830Q | 152-07830 | 3/8" (10)         | 3/8" (10)             | 2.7 (1.2)    | 5 (142)                | 1/4"            | 3/8" (10)               | 10-90 (14-136)               | 90 (122)              |

#### 1/4" SUPER DUTY AIR RATCHET

• Exceptional durability with an advanced head design that virtually eliminates slippage • Urethane grip for comfort and control • Faster rundown with 250 RPM • APPLICATIONS: Under-dashboard work, small engine repair and body shops • ULTIMATE TORQUE: 15 ft./lb.

MFG. NO.

151-00826

ASCOT NO. CP826 151-00826

DESCRIPTION 1/4" Super Duty Air Ratchet

#### 3/8" HEAVY DUTY **AIR RATCHET**

• Advanced motor, full caged gear, and head design • Only 10.7in / 272mm long • Better access to restricted areas • 2.7 lb. / 1.2 RUBBER kg • Adjustable side exhaust BUMPER avoids blowing dirt and dust • Ergonomic composite grip insulates operator's hand from cold • Designed for a variety of applications from heavy ones such as transmission and suspension work to light ones such as engine repair, dashboard work and general maintenance • ULTIMATE TORQUE: 70 ft./lb.



| ASCOT NO. | MFG. NO. | DESCRIPTION                 |
|-----------|----------|-----------------------------|
| 152-07829 | CP7829   | 3/8" Heavy Duty Air Ratchet |
| 153-07829 | CP7829H  | 1/2" Heavy Duty Air Ratchet |



#### 3/8" EXTREME DUTY AIR RATCHET

• Adjustable side exhaust • LOW NOISE LEVEL: Only 79 dBA • One of the highest torques available on the market • CP's Patented TriSpring anti-slip head design

| ASCOT NO. | MFG. NO. | DESCRIPTION          | 152-07830 | Y |
|-----------|----------|----------------------|-----------|---|
| 152-07830 | CP7830Q  | 3/8" Super Duty Rat  | chet      | Ì |
| 153-07830 | CP7830HQ | 1/2" Super Duty Rate | chet      |   |

#### 3/8" QUIET AIR RATCHET

• APPLICATIONS: exhaust systems, small engines, water and fuel pumps and radiator and air conditioner removal and replacement • New advanced, patented head design • Patented ergonomic square-handle design for a comfortable grip • Efficient 1/2 HP motor and triple idler planetary gear system • ULTIMATE TORQUE: 50 ft./lb.

| ASCOT NO. | MFG. NO. | DESCRIPTION            | 152-00828 |   |
|-----------|----------|------------------------|-----------|---|
| 152-00828 | CP828    | 3/8" Quiet Air Ratchet |           | 0 |
| 153-08281 | CP828H   | 1/2" Quiet Air Ratchet |           |   |



The 3/8" Air Ratchet in use.





# Needle Scaler, Cutter, Tire Buffers

#### NEEDLE SCALER

Ideal for surface preparation work
Adjustable sleeve allows needle clearance based on the application • 19 1/8" steel needles with high resistance to wear
Easily converts to a weld flux chipping hammer • BLOWS PER MINUTE: 4,800

ASCOT NO. MFG. NO. DESCRIPTION 157-07120 CP7120 Needle Scaler

#### HIGH SPEED CUTTER

• Adjustable speed regulator for precise control • Lock off throttle to prevent accidental start up • Rear exhaust directs air away from work area • MAX RPM: 22,000

| ASCOT NO. | MFG. NO. | DESCRIPTION  |
|-----------|----------|--|
| 157-00874 | CP874    | High Speed Cutter  |
| 173-00101 | CW1      | Cut-Off Wheel  |
| 173-00220 | CW20     | Arbor for High Speed Cutter (Fits<br>3" & 4" Cut-Off Wheels) |

#### LOW SPEED TIRE BUFFER KIT

• Quick change slip chuck for fast and easy change of buffing wheel • Adjustable speed regulator for precise control • Lock off throttle to prevent accidental start ups • Rear exhaust directs air away from work area • 2,800 RPM

| e speed<br>off | 0         |  |
|----------------|-----------|--|
|                | 158-00873 |  |
| RIPTION        |           |  |

158-00871

| ASCOT NO. | MFG. NO. | DESCRIPTION                |
|-----------|----------|----------------------------|
| 158-00873 | CP873K   | Includes Over Hose         |
| 158-01873 | CP873    | Low Speed Tire Buffer Only |

#### HIGH SPEED TIRE BUFFER KIT

 Jacobs chuck for holding buffing accessories
 Lock-off throttle • APPLICATIONS: tire patchwork, roughing areas for recapping and cleaning tire moldings
 FREE SPEED: 22,000 RPM

| ASCOT NO. | MFG. NO. | DESCRIPTION                 |
|-----------|----------|-----------------------------|
| 158-00871 | CP871K   | Includes Over Hose          |
| 158-01871 | CP871    | High Speed Tire Buffer Only |

# **Grinders & Surface Conditioning Discs**

157-07120

157-00874

#### 417-39120 2" QUICK CHANGE SURFACE CONDITIONING DISCS · Embedded with abrasive grain to eliminate fraying of edges, 417-39121 resist loading and provide a consistent finish • Ideal for flat or contoured surfaces • APPLICATIONS: Light deburring, surface FINE, preparation, blending scratches, removing rust, corrosion and MEDIUM OR oxidation, removing stains from stainless steel, finishing aluminum 417-39122 COARSE and stainless steel • Available in fine, medium or coarse ASCOT NO MEG NO DESCRIPTION 417-39120 3912BLUEF 2" Quick Change Surface Conditioning Discs: Blue (Fine) 417-39121 3912MARNM 2" Quick Change Surface Conditioning Discs: Maroon (Medium) 417-39122 3912BRWNC 2" Quick Change Surface Conditioning Discs: Brown (Coarse) 417-39202 417-39202 392002 Backing Pad for 2" Surface Conditioning Discs



AIR TOOLS

### Grinders & Surface Conditioning Discs (cont.)

#### **GREEN ZIRCONIA DISCS**

• Twist-to-lock backing • Offers longer life and more aggressive results than zirconia or aluminum oxide • Flexible discs resist chipping, snagging and cracking • For use on air grinders and are compatible with all 3M style, Type "R" backing pads • Especially good on extra hard metals • 20,000 RPM • 25 per box

| ASCOT NO. | MFG. NO. | DESCRIPTION                   |
|-----------|----------|-------------------------------|
| 417-12612 | 12612    | 2" Disc, 24 Grit (25 per box) |
| 417-12613 | 12613    | 2" Disc, 36 Grit (25 per box) |
| 417-12614 | 12614    | 2" Disc, 50 Grit (25 per box) |
| 417-12615 | 12615    | 2" Disc, 80 Grit (25 per box) |
| 417-12616 | 12616    | 3" Disc, 24 Grit (25 per box) |
| 417-12617 | 12617    | 3" Disc, 36 Grit (25 per box) |
| 417-12618 | 12618    | 3" Disc, 50 Grit (25 per box) |
| 417-12619 | 12619    | 3" Disc, 80 Grit (25 per box) |

#### 2" SURFACE **CONDITIONING DISCS**

· Best used on aluminum parts • USA MADE • QUANTITY: 25 per box • MAXIMUM ΙΙςδ **OPERATING SPEED: 25,000** 



QTY./BOX

157-00875

|           |          |                    | 417-13004      | 417-13 |
|-----------|----------|--------------------|----------------|--------|
| ASCOT NO. | MFG. NO. | DESCRIPTION        |                |        |
| 417-13003 | 620TE-1  | 2" Conditioning Di | iscs: Brown (( | Coarse |
|           |          |                    |                |        |

| 417-13003 | 620TE-1    | 2" Conditioning Discs: Brown (Coarse)  | 25 |
|-----------|------------|--|----|
| 417-13004 | 622TE-1    | 2" Conditioning Discs: Maroon (Medium) | 25 |
| 417-13005 | 620TE-1-50 | 2" Conditioning Discs: Brown (Coarse)  | 50 |

#### MINI ANGLE DIE GRINDER

· Compact, lightweight design for easy maneuverability • 90° angle head allows flexibility in confined areas • Complete with 1/4" and 6mm collet • APPLICATIONS: high speed blending, smoothing, porting, and deburring in confined areas • MAX RPM: 22,500

MFG. NO. DESCRIPTION ASCOT NO 157-00875 CP875

Mini Angle Die Grinder

#### **MINI DIE GRINDER**

 Compact, lightweight design for easy maneuverability • Adjustable speed regulator for precise control • Complete with 1/4" and 6mm collet • APPLICATIONS: high speed blending, smoothing, porting, and deburring in confined areas • MAX RPM: 30,000

ASCOT NO. MFG. NO. 157-00876 CP876

DESCRIPTION Mini Die Grinder



WARNING: For more information go to www.P65Warnings.ca.gov.

157-00876

#### STRIP-BRITE PADS

· Used for paint or coating removal · Features the quick and easy twist-to-lock attachment system • Open-web construction impregnated with silicon carbide to provide aggressive and long-lasting performance • Threedimensional web has a soft edge, allowing it to remove paint and other coatings in those unreachable creases and dents while removing very little metal • Ideal for stripping paint without damaging metal, especially on aluminum • QUANTITY: 10 per Box



417-16210

DESCRIPTION ASCOT NO MFG NO 417-16210 16210 Purple 2" Strip-Brite Pad 417-16211 16211 Purple 3" Strip-Brite Pad

#### PROFESSIONAL STUD/HUB BRUSH KIT

· Ideal for hub and stud cleaning job with ease · QUICK AND EASY: Change brushes in seconds • Includes a 1/2" drive adapter • Powered by a cordless drill • Replacement brushes available



# Drills



#### 1/4" REVERSIBLE MINI AIR DRILL

 Composite housing with thermoplastic rubber handle grip • Wings on right & left sides to guide the forefinger • Large teasing trigger and progressive valve allowing more control to start holes • Low speed gear box • Flat back part for better pushing action while drilling and tapping • Reverse lever on the top for easier access • Handle exhaust allowing the air to flow away from the operator • Supplied with high quality industrial Jacobs® chucks for longer use • keyed Metal • APPLICATIONS: Excellent for drilling, honing, reaming and hole sawing • FREE SPEED: 3,300 RPM

ASCOT NO. MFG NO 157-07302 CP7300RC

DESCRIPTION 1/4" Reversible Mini Air Drill

157-07302

#### 3/8" REVERSIBLE DRILL

- · Teasing throttle for precise control
- APPLICATIONS: Screwdriving, honing and heavy
- drilling FREE SPEED: 2,600 RPM

ASCOT NO.

157-01879

| ASCOT NO. |           | DESCRIPTION           |
|-----------|-----------|-----------------------|
| 157-78926 | CP789-R26 | 3/8" Reversible Drill |
|           |           |                       |

157-78926

TEASING

THROTTLE

#### 3/8" REVERSIBLE ANGLE DRILL

· Composite housing with thermoplastic rubber handle grip • Lock-off throttle for more controlled BUILT-IN applications • Built-in Forward-FORWARD-Reverse ring • Compact low REVERSE profile head to get into confined spaces • Handle exhaust allowing the air to flow away from the operator • Supplied with high quality industrial Jacobs<sup>®</sup> chucks for longer use • APPLICATIONS: Excellent for drilling and screw driving in confined areas • FREE SPEED: 2,000 RPM

MFG. NO.

CP879C

157-01879

#### 1/4" MINI AIR DRILL

· Composite housing with thermoplastic rubber handle grip • Wings on right & left sides to guide the forefinger • Large teasing trigger and progressive valve allowing more control to start holes • Low speed gear box • Flat back part for better pushing action while drilling and tapping • Handle exhaust allowing the air to flow away from the operator • Supplied with high quality industrial Jacobs® chucks for longer use • keyed Metal • APPLICATIONS: Excellent for drilling, honing, reaming and hole sawing • FREE SPEED: 3,300 RPM

MFG. NO.

CP7300C



157-17302

|   | Clease Poenatic<br>Classic<br>Dates 1907 |
|---|--|
| 1/2" REVERSIBLE DRILL   | (O)                                      |
| <ul> <li>Teasing throttle for precise control</li> <li>APPLICATIONS: heavy drilling, reaming,<br/>hole sawing and jobs requiring a lot<br/>of torque • FREE SPEED: 500 RPM</li> </ul> |  |
| ASCOT NO. MFG. NO. DESCRIPTION  |  |
| 157-00789 CP789-HR 1/2" Reversible Drill  | 157-00789                                |

DESCRIPTION

3/8" Reversible Drill



**NIR TOOLS** 

ASCOT NO.

157-17302

DESCRIPTION


1/4" Mini Air Drill






# **Air Tool Accessories**

HAMMER ACCESSORIES



| INDEX NO. | ASCOT NO. | MFG. NO.  | DESCRIPTION             |
|-----------|-----------|-----------|-------------------------|
| 1         | 171-47050 | A-047050  | Rivet Cutter            |
| 2         | 171-47051 | A-047051  | Wide Cutting Chisel     |
| 3         | 171-47052 | A-047052  | Bushing Splitter        |
| 4         | 171-47057 | A-047057  | U-Joint & Tie Rod Tool  |
| F         | 171-47059 | A-047059  | 1" Separator Fork       |
| 5         | 171-47061 | A-047061  | 1-1/4" Separator Fork   |
| 6         | 171-47071 | A-047071  | Twin Blade Cutter       |
| 7         | 171-47073 | A-047073  | Cold Chisel             |
| 8         | 171-47074 | A-047074  | Straight Punch          |
| 9         | 171-47078 | A-047078  | Tapered Punch           |
| 10        | 171-47091 | A-047091  | 1-1/4" Smoothing Hammer |
| 11        | 171-47095 | A-047095  | Quick-Change Retainer   |
|           | 171-47096 | A-047096  | Bee-Hive Retainer       |
| 12        | 171-47270 | CA-047270 | 2' Leader Hose          |
| 12        | 171-47300 | CA-047300 | Quick Change Coupler    |
|           | 171-47032 | CA-047302 | Nipple                  |





# RPG,

#### **RPG** 1" DRIVE & #5 SPLINE SUPER DUTY AIR IMPACT WRENCH

- 6" extended anvil
- Steel end plates
- WORKING TORQUE RANGE: 1,600-1,800 ft./lb.
- FREE SPEED: 4,500 RPM
- MAXIMUM TORQUE: 1,800 ft./lb.

#### RPG 1" DRIVE MINI PLUS AIR IMPACT WRENCH

- 6" extended anvil
- 3-position power setting
- Rubber-coated side handle for added comfort
- Powered by the twin hammer clutch
- FREE SPEED: 5,000 RPM
- MAXIMUM TORQUE: 2,000 ft./lb.

#### RPG 1" & #5 SPLINE DRIVE SUPER DUTY IMPACT WRENCH

- 6" extended anvil
- 3-position forward and reverse
- High efficiency 6-vane motor
- Swoop-back side handle for maneuverability and balance
- Pinless clutch mechanism
- WORKING TORQUE RANGE: 1,800-2,000 ft./lb.
- FREE SPEED: 5,000 RPM
- MAXIMUM TORQUE: 2,000 ft./lb.

| ASCOT NO. | MFG. NO. | SQUARE<br>DRIVE | FREE SPEED<br>(RPM) | MAX TORQUE<br>(FT./LB.) | AIR PRESSURE<br>(PSI) | AIR CON. AVG<br>(CFM) | AIR INLET<br>(NPT) | HOSE SIZE | LENGTH | WEIGHT<br>(LB.) |
|-----------|----------|-----------------|---------------------|-------------------------|-----------------------|-----------------------|--------------------|-----------|--------|-----------------|
| 155-12856 | A2856    | 1"              | 5,000               | 2,000                   | -                     | 12                    | 1/2"               | 3/4"      | 20.5″  | 27.6            |
| 155-17786 | A778-6   | 1″              | 4,500               | 1,800                   | 90                    | 8.4                   | 1/2"               | 3/4"      | 20.3"  | 26.59           |
| 155-26464 | A26464   | 1″              | 5,000               | 1,800                   | 90                    | 9                     | 1/2"               | 3/4"      | 19.2"  | 17.86           |
| 156-12856 | A2856SP  | #5 Spline       | 5,000               | 2,000                   | -                     | 12                    | 1/2"               | 3/4"      | 20.5″  | 27.6            |
| 156-17786 | A778SP-6 | #5 Spline       | 4,500               | 1,800                   | 90                    | 8.4                   | 1/2"               | 3/4"      | 20.3"  | 26.59           |







#### **RPG** 1/2" DRIVE SUPER DUTY **AIR IMPACT WRENCH**

- 2" extended anvil
- FREE SPEED: 8000 RPM
- MAXIMUM TORQUE: 600 ft./lb.
- Proven design and the most popular configuration in the tire service industry
- Powered by the durable and high performing twin hammer mechanism
- Handle exhaust

#### **RPG** 1/2" DRIVE COMPOSITE IMPACT WRENCH W/ EXTENDED ANVIL

- Convenient one-hand operated forward/reverse push button
- Four-setting torque adjustment switch
- Compact with a total length of only 7.2"
- Twin hammer mechanism provides smooth balance
- Feather trigger for precise speed control
- · Energy efficient motor for maximum performance & long life
- Swivel air inlet prevents hose from twisting



#### IMPACT WRENCH SPECIFICATIONS

| ASCOT NO. | MFG. NO.    | SQUARE<br>DRIVE | FREE SPEED<br>(RPM) | MAX TORQUE<br>(FT./LB.) | AIR PRESSURE<br>(PSI) | AIR CON. AVG<br>(CFM) | AIR INLET<br>(NPT) | HOSE SIZE | LENGTH | WEIGHT<br>(LB.) |
|-----------|-------------|-----------------|---------------------|-------------------------|-----------------------|-----------------------|--------------------|-----------|--------|-----------------|
| 153-12260 | A2131-2COMP | 1/2"            | 7,500               | 685                     | 90                    | 5                     | 1/4″               | 3/8"      | 7.2"   | 4.5             |
| 153-23120 | A2312       | 1/2"            | 8,000               | 600                     | 90                    | 4                     | 1/4″               | 3/8"      | 8-1/8" | 5.6             |
| 153-23121 | SS-A2312    | 1/2″            | 8,000               | 600                     | 90                    | 4                     | 1/4″               | 3/8"      | 6.1″   | 5.9             |





## **RPG Parts & Accessories**





175-10037



175-10043



REPLACEMENT PARTS FOR 4778-6 1" DRIVE IMPACT WRENCH Set of 6 Rotor Blades for A778-6 1" Drive Impact Wrench 175-10026 #26 175-10037 #37 Hammer for A778-6 1" Drive Impact Wrench 175-10040 #40 Hammer Cage for A778-6 1" Drive Impact Wrench 175-10043 #43 Replacement Side Handle Kit for A778-6 1" Drive Impact Wrench 176-18406 A778-6TK Tune-Up Kit for A778-6 1" Drive Impact Wrench

DESCRIPTION

ASCOT NO. MFG. NO.

175-23104





| ASCOT NO. | MFG. NO.  | DESCRIPTION  |
|-----------|-----------|--|
| 175-23104 | JB-04Blue | Blue Protective Boot for RPG A2312 Impact Wrenches |
| 175-82651 | H-082651  | 1" Impact Wrench Retainer Clip O-Ring              |
| 175-83071 | P-08371   | O-Ring for 1/2" Impact Wrench Retainer Clips       |







#### **RPG** LOW SPEED TIRE **BUFFER WITH QUICK CHANGE SLIP CHUCK**

• Brass bushings provide performance and durability in tough working conditions • Includes whip hose and exhaust hose • Quick change slip chuck for fast and easy change of buffing wheel • Built-in regulator • Lock off throttle to prevent accidental start ups • Rear exhaust directs air away from the work area • Ideal for patchwork, roughing areas for recapping and cleaning tire moldings • Overhose Kit also Available Separately (175-00873)



# 158-10871

#### **RPG** HIGH SPEED TIRE BUFFER WITH **OVERHOSE KIT**

 Jacobs chuck for holding buffing accessories • Lock-off throttle • FREE SPEED: 22,000 RPM • APPLICATIONS: Tire patchwork, roughing areas for recapping and cleaning tire moldings • Includes overhose kit



#### **RPG** HIGH SPEED **BUFFER KIT WITH QUICK** CHANGE CHUCK

 Quick change chuck for holding buffing accessories • Lock-off throttle • FREE SPEED: 22,000 RPM • APPLICATIONS: Tire patchwork, roughing areas for recapping and cleaning tire moldings • Includes overhose kit



175-18713 175-28713

| ASCOT NO. | MFG. NO.    | DESCRIPTION   |
|-----------|-------------|---|
| REPLACE   | MENT PARTS  | FOR AIR BUFFERS                                       |
| 175-00873 | A-873K-0H   | Overhose Kit for<br>Tire Buffers                      |
| 175-18713 | A8713-TA    | Trigger Assembly<br>for Tire Buffers                  |
| 175-28713 | SQC01       | Replacement 7/16"<br>Quick Change<br>Slip Chuck       |
| ACCE      | SSORIES FOR | AIR BUFFERS   |
| 173-00018 | QC18        | Quick Chuck<br>Adapter W/ Collar                      |
| 173-00019 | QC19        | Quick Chuck Adapter<br>W/ Spacer, 1" x<br>3/8" Thread |
| 173-00020 | QC20        | Quick Chuck Adapter<br>For 1/8″ Shank                 |
| 173-00022 | QC22        | Quick Chuck Adapter<br>For 1/4″ Shank                 |
| 173-00023 | QC23        | Quick Chuck Adapter<br>For 5/16″ Shank                |

#### TIRE BUFFER SPECIFICATIONS

| ASCOT NO. | MFG. NO. | DESCRIPTION                                   | FREE SPEED<br>(RPM) | LENGTH |
|-----------|----------|---|---------------------|--------|
| 158-10873 | A873K    | Low Speed Tire Buffer with Quick Change Chuck | 2,800               | 1.75″  |
| 158-10871 | A871K    | High Speed Tire Buffer with Overhose kit      | 22,000              | 2.5"   |
| 158-11871 | A871K-QC | High Speed Buffer Kit with Quick Change Chuck | 22,000              | 1.75″  |



### <sup>56</sup> AIR TOOLS









#### **RPG** 3"CUT-OFF TOOL

• Adjustable speed regulator for precise control • Lockoff throttle to prevent accidental start-up • Rear exhaust directs air away from work area • Durable gears for top performance and long life • FREE SPEED: 22,000 RPM



#### **RPG** 1/4" MINI ANGLE DIE GRINDER

• Compact, lightweight design for easy use • APPLICATIONS: High speed blending, smoothing, porting and deburring in confined areas • Right angle for easy maneuvering • FREE SPEED: 22,000 RPM

#### **RPG** WHEEL WEIGHT ADHESIVE **REMOVAL TOOL**

• High torque motor to cut through stubborn wheel weight adhesive, body pinstripes, etc. • High RPM to prevent pad from bogging down • Pad made of a tough and long-lasting material • Rubberinsulated motor housing for hand comfort • Lock-off trigger for added safety • Includes eraser pad • SPINDLE THREAD: 5/16"-24



#### PARTS & ACCESSORIES





#### **AIR TOOL SPECIFICATIONS**

| ASCOT NO. | MFG. NO. | FREE SPEED<br>(RPM) | AIR PRESSURE<br>(PSI) | AIR CON. AVG<br>(CFM) | AIR INLET<br>(NPT) | HOSE SIZE | LENGTH | WEIGHT<br>(LB.) |
|-----------|----------|---------------------|-----------------------|-----------------------|--------------------|-----------|--------|-----------------|
| 157-03252 | A143252  | 3,700               | 90                    | 4                     | 1/4"               | 3/8"      | 7.9″   | 1.8             |
| 157-10874 | A874     | 22,000              | 90                    | 5                     | 1/4″               | 3/8"      | 7.25"  | 1.75            |
| 157-10875 | A875     | 22,000              | 90                    | 5                     | 1/4″               | 3/8"      | 5″     | 1               |



AIR TOOLS



# Impact Wrenches

### 1/2" Super Duty **Air Impact Wrench**

- Most popular tool in its class
- Offers the sheer power and performance • features to tackle the toughest of jobs
- Durable and economical
- TORQUE RANGE: 25-350 ft./lb.

| ASCOT NO. | MFG. NO.   | DESCRIPTION    |
|-----------|------------|----------------|
| 153-00231 | IR-231HA   | Standard Anvil |
| 153-02312 | IR-231HA-2 | Extended Anvil |

ECONOMICAL DURABLE TOUGH

153-00231

#### 1/2" SUPER DUTY **AIR IMPACT WRENCH**

 APPLICATIONS: For tire-changing, shock and spring work, front-end work and other heavy automotive and truck work • Pumps out 500 ft./lb. of torgue at a free speed of 7,000 RPM • IR-244A-2 with a two-inch extended anvil for use with flip sockets

| ASCOT NO. | MFG. NO.  | DESCRIPTION    | 4         |
|-----------|-----------|----------------|-----------|
| 153-00244 | IR-244A   | Standard Anvil | 153-00244 |
| 153-02442 | IR-244A-2 | Extended Anvil | 155-00244 |

#### 1/2" SUPER DUTY **AIR IMPACT WRENCH**

• Punish the toughest bolts with 780 ft./lb. of max reverse torgue and 1,100 ft./lb. of nut-busting torgue, all powered by Ingersoll Rand's finely tuned motor and twin-hammer impact mechanism • At only 4.3 pounds, the 2135QXPA is as light as it is powerful so your hand tires less, letting you get more work done • Ingersoll Rand's Quiet Technology reduces the sound of the tool, sparing your ears without sacrificing a single ounce of power



| ASCOT NO. | MFG. NO.      | DESCRIPTION    |  |  |
|-----------|---------------|----------------|--|--|
| 153-22135 | IR-2135QXPA   | Standard Anvil |  |  |
| 153-32135 | IR-2135QXPA-2 | Extended Anvi  |  |  |

BUYER'S GUIDE ASCOT SUPPLY CORPORATION

#### 1/2" ULTRA DUTY TITANIUM AIR IMPACT WRENCH

• Titanium weighs less and provides greater durability • Enhanced Twin Hammer mechanism for fast removal of frozen bolts • Push button forward/reverse controls for one-handed operation • TORQUE RANGE: 50-600 ft./lb., 625 ft./lb. max (forward), 700 ft./lb. max (reverse)

153-12235

| ASCOT NO. | MFG. NO.        | DESCRIPTION                          |
|-----------|-----------------|--------------------------------------|
| 153-02235 | IR-2235TiMAX    | Standard Anvil                       |
| 153-12235 | IR-2235TiMAX-2  | 2" Extended Anvil                    |
| 153-32235 | IR-2235QTiMAX   | Quiet Version                        |
| 153-22235 | IR-2235QTiMAX-2 | Quiet Version with 2" Extended Anvil |
| 153-42235 | IR-2235TiMAX-2  | 2" Extended Anvil                    |

#### 3/4" SUPER DUTY AIR IMPACT WRENCH

 Non-biased motor delivers 1.050 ft./ lb. of maximum torque in both forward and reverse • Two power settings in forward and reverse • Variable speed trigger • Lighter than other 3/4" impacts in its class • Handle-vented exhaust directs air away from the operator • Silenced exhaust reduces tool noise while in use

| ASCOT NO. | MFG. NO. | DESCRIPTION                       |
|-----------|----------|-----------------------------------|
| 154-00259 | IR-259   | 3/4" Super Duty Air Impact Wrench |





| 2135 | IR-2135QXPA-2 | Extended Anvil |  |
|------|---------------|----------------|--|
|      |               |                |  |
|      |               |                |  |



#### 3/4" SUPER DUTY AIR **IMPACT WRENCH**

• Powerful 3/4" wrench • Combines compact size with high output • Ideal for everything from spring work to pinion nut and track pad removal and major engine teardowns • Jumbo hammer mechanism delivers up to 1,100 ft./ lb. of torque smoothly, with less vibration



| ASCOT NO. |           | MFG. NO. | DESCRIPTION       |  |  |  |
|-----------|-----------|----------|-------------------|--|--|--|
|           | 154-00261 | IR-261   | Standard Anvil    |  |  |  |
|           | 154-02613 | IR-261-3 | 3" Extended Anvil |  |  |  |
|           | 154-02616 | IR-261-6 | 6" Extended Anvil |  |  |  |

#### 3/4" MAXIMUM IMPACT AIR IMPACT WRENCH

• 3/4" Maximum Impact Air Impact Wrench • 1350 ft./lb. maximum reverse torque from a tool that weighs just 7.4 lb. and is compact enough to access tight spaces • Built to last and designed to withstand tough use in rugged environments • An air motor that's 16% more efficient than its predecessor and an easy-to-clean inlet screen means less downtime, better tool performance, and less money spent on compressed air • TORQUE RANGE: 200-900 ft./lb.



#### 1" HEAVY DUTY AIR IMPACT WRENCH

• Improved 1" drive tool perfect for truck and heavy equipment maintenance • Offers power and convenience at an affordable price • Compact, lightweight and perfect for working on suspension components • TORQUE RANGE: 100-1000 ft./lb.

| ASCOT NO. | MFG. NO. | DESCRIPTION     |
|-----------|----------|-----------------|
| 155-00295 | IR-295   | Standard Anvil  |
| 156-02951 | IR-295-S | #5 Spline Drive |

#### 1" D-HANDLE IMPACT WRENCH

CORE DESIGN

• SOLID STEEL IMPACT MECHANISM: Deliver 2,100 ft./lb. of torque • HIGHLY ENGINEERED DESIGN: Delivers the power you need over the life of the tool • STEEL CORE DESIGN: Nothing's been proven to last longer • CHEMICAL RESISTANT HOUSING & STEEL CORE: Stands up to drops and harsh work environments • LIGHTWEIGHT: 25% lighter than the industry's leading 1" wrench • 360° ADJUSTABLE HANDLE: The side handle rotates fully around the tool as the job demands • SWIVEL HOSE CONNECTION: Keeps cords from getting tangled so you can move freely around the garage • 6" ANVIL EXTENSION: Increases accessibility in hard to reach places

| ASCOT NO. | MFG. NO.       | DESCRIPTION       |
|-----------|----------------|-------------------|
| 154-12145 | IR-2145QiMAX   | Standard Anvil    |
| 154-22145 | IR-2145QiMAX-3 | 3" Extended Anvil |
| 154-32145 | IR-2145QiMAX-6 | 6" Extended Anvil |

#### 3/4" ULTRA DUTY AIR IMPACT WRENCH

 Offers all of the ergonomic, power and durability enhancing features as the IR-2161 but with a 6" extended anvil for those hard to reach applications • Jumbo hammer mechanism • Up to 1,200 ft./lb. of torgue Trouble-free, longer performance aided by the pressure-feed lube system • Compact and only 7-5/8" long • Handle exhaust

EXTRA PERFORMANCI 154-21617

ASCOT NO. 154-21617

DESCRIPTION IR-2161XP-6 3/4" Ultra Duty Air Impact Wrench



155-02850



MFG. NO.



#### Impact Wrenches (cont.)

### 1" Heavy Duty Air Impact Wrench

- Combines exceptional power, durability and operator convenience
- Delivers 1450 ft./lb. of maximum torque at 90 psi (1770 ft./lb. max torque at 120 psi) with a 5000 RPM free speed and four-position regulator 360° swivel inlet
- Chemical resistant boot
- Available in 6" extended anvil and 6" extended #5 spline anvil A1:089 or high production truck tire changing

| ASCOT NO. | MFG. NO.   | DESCRIPTION                |
|-----------|------------|----------------------------|
| 155-28560 | IR-285B    | Standard Anvil             |
| 155-02856 | IR-285B-6  | 6" Extended Anvil          |
| 156-28566 | IR-285BS-6 | #5 Spline Super Duty Anvil |

155-02856

#### 1" ULTRA DUTY AIR IMPACT WRENCH

 APPLICATIONS: Most powerful 1" wrench for spring work, tractor pads, bus maintenance and off-road/farm equipment
 MAXIMUM TORQUE: 2000 ft./lb.

| ASCOT NO. | MFG. NO. | DESCRIPTION     | 155-00293 |
|-----------|----------|-----------------|-----------|
| 155-00293 | IR-293   | Standard Anvil  |           |
| 156-02931 | IR-293-S | #5 Spline Drive |           |



#### 1" SUPER DUTY AIR IMPACT WRENCH

1" drive wrench with 1,000 ft./lb.
torque to handle tough jobs in cramped spaces
Built-in pressure-feed lube system, adjustable side
handle and built-in oil reservoir that provides continuous
misting of the air motor • Available in 6" extended anvil and 6"
extended #5 spline drive anvil for high production truck tire changing

| ASCOT NO. | MFG. NO.  | DESCRIPTION                |
|-----------|-----------|----------------------------|
| 155-00280 | IR-280    | Standard Anvil             |
| 155-02806 | IR-280-6  | 6" Extended Anvil          |
| 156-28006 | IR-280-S6 | #5 Spline Super Duty Anvil |

#### 1" SUPER DUTY AIR IMPACT WRENCH

Designed for getting into cramped spaces with three-way adjustable handle
Ideal for spring work, tractor pads, bus maintenance and off-road/farm equipment
TORQUE RANGE: 150-1000 ft./lb. (1600 maximum)

| ASCOT NO. | MFG. NO. | DESCRIPTION    | 155-00290 |
|-----------|----------|----------------|-----------|
| 155-00290 | IR-290   | Standard Anvil |           |
| 156-02901 | IR-290-S | #5 Spline      |           |

BUYER'S GUIDE







# **IR Cordless Tools**

#### 1/2" CORDLESS IMPACT WRENCH

- 780 ft./lb. reverse torque and 1100 ft./lb. nut-busting torque from a tool weighing just 6.8 lb., best power to weight ratio in its class.
- High-efficiency rare earth magnet motor, high-capacity variable . speed trigger, all-metal drive train, and metal-reinforced housing enable this tool to stand up to the toughest jobs.
- . Optimized balance combined with an ergonomic handle and soft touch over-molded grip provide increased comfort in extended use.





| ASCOT NO. | MODEL | BATTERIES<br>INCLUDED | DRIVE SIZE                                 | ANVIL       | MAX TORQUE<br>FT./LB. | FREE SPEED<br>(RPM) | BPM  | LENGTH IN. | WEIGHT  |
|-----------|-------|-----------------------|--|-------------|-----------------------|---------------------|------|------------|---------|
| 153-71521 | W7152 | 1                     | 1/2"<br>(Socket Retaining Ring)            | Standard    | 1000 (1,360)          | 0-1900              | 2450 | 6.7        | 8.1 lb. |
| 153-72522 | W7252 | 1                     | 1/2"<br>(Socket Retaining<br>Ring, 2" Ext) | 2" Extended | 1000 (1,360)          | 0-1900              | 2450 | 8.1        | 8.1 lb. |

#### 1" CORDLESS IMPACT WRENCH

- Remove hoses & trip hazards to keep operators & technicians safe .
- World's Most Powerful 1" Cordless Impact Wrench with best in class power-to-weight ratio
- 250 bolts per charge tackle a full day's worth of work
- 3,000 ft-lbs of nut busting torque, 2,200 ft-lbs of tightening torque
- IP56 rated for tough environmental conditions
- IQv Power Control System includes 3 modes: . MAX Power, MID, and Snug
- 360° adjustable D-handle: rotates fully around the tool as the job demands



| ASCOT NO. | MODEL     | BATTERIES<br>INCLUDED | DRIVE SIZE | ANVIL       | MAX TORQUE<br>FT./LB. | FREE SPEED<br>(RPM) | BPM  | LENGTH IN. | WEIGHT |
|-----------|-----------|-----------------------|------------|-------------|-----------------------|---------------------|------|------------|--------|
| 153-94911 | W9491-K4E | 1                     | 1" Square  | Standard    | 2600 ft./lbs.         | 890                 | 1170 | 20-1/8″    | 38.3   |
| 153-96911 | W9691-K4E | 1                     | 1" Square  | 6" Extended | 3000 ft./lbs.         | 890                 | 1170 | 26-1/8″    | 39.9   |



153-96911



# Milwaukee Cordless Tools

#### CORDLESS 1/2" DRIVE IMPACT WRENCH

• 4 CUSTOMIZABLE MODES: Provides multiple fastening torque outputs designed for sedans, light trucks and box trucks

- POWERSTATE™ BRUSHLESS MOTOR: Delivers up to 750 ft./ lb. of fastening torque and 1,100 ft./lb. of nut-busting torque
- LONG MOTOR LIFE: POWERSTATE™ Brushless Motor delivers maximum power and long motor life

 FASTER TIRE SERVICE: Enables users to perform faster tire service by removing the hassle of pneumatic hoses, compressors, and torque sticks

• PART OF THE M18<sup>™</sup> SYSTEM: Featuring over 175+ Tools

#### 1" DRIVE EXTENDED ANVIL D-HANDLE IMPACT WRENCH

• POWERSTATE<sup>™</sup> Brushless Motor delivers up to 2,000 ft-lbs of nut-busting torque and 1,900 ft-lbs of fastening torque

- Install up to 200 1-1/4" bolts on a single HIGH OUTPUT™ HD12.0Ah battery
- The 4-Mode DRIVE CONTROL<sup>™</sup> provides you with greater control over the output speed and power of the MILWAUKEE® High Torque Impact Wrench
- The ONE-KEY<sup>™</sup> Technology allows you to customize, track, and manage the impact wrench with the ability to set a repeatable torque output for maximum control







SUPPLY CORPORATION

| ASCOT NO. | MFG. NO. | DESCRIPTION  | ASCOT NO. | MFG. NO. | DESCRIPTION   |
|-----------|----------|--|-----------|----------|---|
| 153-76920 | 2769-20  | Cordless 1/2" Drive Impact Wrench –<br>2" Extended Anvil (Bare Tool) | 155-86920 | 2869-20  | 1" Drive Extended Anvil D-Handle<br>Impact Wrench (Bare Tool) |
| 153-76922 | 2769-22  | Cordless 1/2" Drive Impact Wrench<br>– 2" Extended Anvil (Kit)       | 155-86922 | 2869-22  | 1" Drive Extended Anvil D-Handle<br>Impact Wrench (Kit)       |





#### CORDLESS LOW SPEED BUFFER KIT

- Dedicated buffing and drilling
- 2-Mode Drive Control<sup>™</sup>
- Drilling Mode: 1,200 RPM
- Buffing Mode: 2,500 RPM
- Runtime to complete up to 30 flat repairs on a single XC4.0Ah battery
- · Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- Compatible with all M12<sup>™</sup> batteries & chargers

158-40922

- POWERSTATE<sup>™</sup> Brushless Motor
- REDLINK PLUS<sup>™</sup> Electronic Intelligence:
- REDLITHIUM<sup>™</sup> batteries:

SUPPLY CORPORATION

Kit includes: Low Speed Tire Buffer, M12™ REDLITHIUM™ CP2.0 Battery, . M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC 4.0 Extended Capacity Battery Pack, M12<sup>™</sup> Lithium-ion Battery Charger, Quick Change Adapter, Carrying Case

Tilwaukee

M12 FUEL

#### COMMERCIAL TIRE FLAT REPAIR KIT

- · Designed to deliver you increased productivity for high volume commercial flat repairs that commercial tire technicians demand
- Kit includes: M12 FUEL<sup>™</sup> Low Speed Tire Buffer (2409-20), M12 FUEL<sup>™</sup> 1/2" Drill Driver (Tool Only) (2503-20), Quick Change Adapter, M12<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery (48-11-2420), M12<sup>™</sup> REDLITHIUM<sup>™</sup> XC 4.0 Extended Capacity Battery Pack(48-11-2440), M12<sup>™</sup> Lithium-ion Battery Charger (48-59-2401) & Carrying Case

ilmaukee

M12 FLIEL

158-45922

HIGH VOLUME

REPAIRS







### Milwaukee Power Tools (cont.)

#### CORDLESS 1/4" HIGH SPEED RATCHET KIT

Our M12 FUEL<sup>™</sup> 1/4" High Speed Ratchet Kit is part of the latest addition to our best-in-class lineup of ratchets. This MILWAUKEE® cordless ratchet kit features the fastest speed while installing and removing fasteners. The most compact head size in its class gives you more access in tight spaces. A steel yoke housing and POWERSTATE™ Brushless Motor deliver the superior durability that you expect from Milwaukee. The M12 FUEL™ High Speed Ratchets are an ideal addition to any technician tool chest, allowing you to be more productive than any other battery-powered ratchet.

#### CORDLESS 3/8" RATCHET TOOL KIT

 MOST POWERFUL: Delivers industry leading torque output of up to 40 ft./lb. • MOST COMPACT: Up to 20% smaller head size • MOST DURABLE: Worlds 1st brushless ratchet provides 2x longer motor life • Best-in class torque to head size ratio • Premium metal components for longer durability



#### M18 CORDLESS TIRE INFLATOR

- Fastest 18V Cordless Tire Inflator: Top off 33" light truck tires in under 1 minute Truefill<sup>™</sup> Technology: Auto pressure check feature activates to ensure PSI target is achieved, automatic shut-off at selected PSI prevents overinflation
- Tire capacity: Premium components and unmatched durability to handle tires over 100 PSI, rated for 150 PSI max
- Optimized for passenger, light truck and other medium duty tires
- PSI memory preset: Save your most used PSI rating with up to 4 PSI slots
- On-board hose & nozzle storage: easily store 36" hose and attachments
- Accessories: Includes all brass Schrader chuck, inflation needle, inflator nozzle & Presta chuck
- Anti-vibration feet: minimize tool walk while in use
- Fits all M18<sup>™</sup> Batteries

ASCOT NO. MFG. NO. DESCRIPTION 477-84820 2848-20 M18 Cordless Tire Inflator





**BUYER'S GUIDE** ASCOT SUPPLY CORPORATION



#### M18 LITHIUM 3.0AH HIGH **OUTPUT BATTERY**

 REDLINK<sup>™</sup> INTELLIGENCE: Our battery circuitry provides optimized performance and overload protection using total system communication between tool, battery and charger • BEST-IN-CLASS CONSTRUCTION: Offers long-lasting performance and the best protection against jobsite, weather and environmental conditions FUEL GAUGE ONBOARD: Displays remaining run-time • VERSATILITY: Powers all 175+ M18<sup>™</sup> cordless solutions • Compatible with all M18<sup>™</sup> tools • 2 year battery warranty

#### M18 LITHIUM 5.0AH **BATTERY PACK**

• REDLINK<sup>™</sup> INTELLIGENCE: Provides optimized performance and overload protection using total system communication between tool, battery and charger • BEST-IN-CLASS CONSTRUCTION: Offers long-lasting performance and durability • FUEL GAUGE ONBOARD: Displays remaining runtime for less downtime on the job • ALL-WEATHER PERFORMANCE: Delivers fade free power in extreme jobsite conditions • VERSATILITY: Powers more than 175+ Milwaukee® M18™ cordless power tools • Ground transport only

#### M18 LITHIUM HD12.0 HIGH **OUTPUT BATTERY**

• The M18 REDLITHIUM<sup>™</sup> HIGH OUTPUT<sup>™</sup> HD12.0 is the best performing cold weather pack ever made, providing increased power in extreme cold weather conditions (below OF / -18C) • Provides the most work per charge of any professional power tool battery in the industry, driving full corded replacement on the jobsite • The REDLITHIUM<sup>™</sup> HIGH OUTPUT<sup>™</sup> HD12.0 battery is fully compatible with 150+ M18<sup>™</sup> solutions





#### M12 LITHIUM BATTERIES

• REDLINK<sup>™</sup> INTELLIGENCE: Provides optimized performance and overload protection using total system communication between tool, battery and charger • BEST-IN-CLASS CONSTRUCTION: Offers long-lasting performance and durability • ALL-WEATHER PERFORMANCE: Delivers fade-free power in extreme job site conditions VERSATILITY: Powers 70+ Milwaukee M12 cordless solutions

| ASCOT NO. | MFG. NO.   | DESCRIPTION                     |
|-----------|------------|---------------------------------|
| 345-12430 | 48-11-2430 | M12 Lithium 3.0 Compact Battery |
| 345-12440 | 48-11-2440 | M12 Lithium XC4.0               |
| 345-12460 | 48-11-2460 | M12 Lithium XC6.0               |



AIR TOOLS



# Air Hammers & Die Grinders

SUPFR

DUTY

POWER

#### SUPER DUTY **AIR HAMMER**

 APPLICATIONS: For front-end and heavy exhaust work, riveting, king pin removal, bushing driving and bolt shearing • Controls starting strokes precisely with an extra-sensitive tease throttle • Super duty power, at up to 1,725 blows per minute • CHISEL SHANK DIAMETER: .401"

DESCRIPTION ASCOT NO. MFG. NO. 159-00132 IR-132

Super Duty Air Hammer

159-00132

157-00125

171-01161

#### HEAVY DUTY ANGLE **AIR DIE GRINDER**

• For work in confined areas • Features a right angle head • APPLICATIONS: For grinding,

porting, polishing, de-burring, breaking sharp edges • Selflocking throttle lever • Positive grip 1/4" capacity collet chuck

ASCOT NO. MFG. NO. 157-00302 IR-302B

DESCRIPTION Heavy Duty Angle Air Die Grinder

FOR WORK

IN CONFINED

AREAS

#### HEAVY DUTY AIR **DIE GRINDER**

• APPLICATIONS: Designed for porting, light weld grinding and breaking sharp edges • 25,000 RPM • Self-locking throttle lever • Positive grip 1/4" capacity collet chuck with two collet wrenches

ASCOT NO MFG NO 157-00308 IR-308B DESCRIPTION Heavy Duty Air Die Grinder



157-00302





# **AIR TOOLS**

#### **NEEDLE SCALER**

 APPLICATIONS: For surface preparation work involving the cleaning or removal of paint, rust, dirt or weld slag • Durable, dependable and economical

| PI        | FOR<br>URFACE<br>REP AND<br>LEANING | DURA        |  |
|-----------|-------------------------------------|-------------|--|
| ASCOT NO. | MFG. NO.                            | DESCRIPTION |  |

157-00125

BUYER'S GUIDE

DESCRIPTION IR-125 Needle Scaler

#### **AIR HAMMER KITS**

· Five-piece chisel set in a plastic pouch with .401" shank diameters • INCLUDES: Edging Tool, Tail Pipe Cutter, Straight Chisel, Cutting Chisel and Pouch

### FIVE-PIECE CHISEL SE

| ASCOT NO. | MFG. NO. | DESCRIPTION            |
|-----------|----------|------------------------|
|           |          |                        |
| 171-01151 | IR-115K  | IR-115 Air Hammer Kit  |
|           |          |                        |
| 171-01161 | IR-116K  | IR-116 Air Hammer Kit  |
| 171-01171 | IR-117K  | IR-117 Air Hammer Kit  |
| 1/1 0/1/1 |          | IN IN AI HUIIIIIEI KIL |
|           |          |                        |

ASCOT SUPPLY CORPORATION

▲WARNING: For more information go to www.P65Warnings.ca.gov.



# **Finishing Tools & Air Drills**

#### 3/8" HEAVY DUTY AIR DRILL



**TIRE BUFFERS** 



### Finishing Tools & Air Drills (cont.)



#### HEAVY DUTY AIR ANGLE SANDER 7" PAD

• Heavy-duty motor handles tough jobs • Lightweight at only 4.5 lb. (2.04 kg.) • Ball Bearing construction for increased tool life • APPLICATIONS: rouging body filler, removing rust, and smoothing welds



| ASCOT NO. | MFG. NO. | DESCRIPTION                        |
|-----------|----------|------------------------------------|
| 157-00313 | IR-313A  | Heavy Duty Air Angle Sander 7" Pad |

#### HEAVY DUTY DUAL ACTION QUIET AIR SANDER 6" PAD

- A built-in silencer muffles noise as you work
- APPLICATIONS: Quality sander used for feather edging,
- metal preparation and finish work on body filler



158-00311

ASCOT NO. 158-00311 DESCRIPTION Heavy Duty Dual Action Quiet Air Sander 6" Pad ASCOT NO. MFG. NO. DI 158-03012 | IR-301-2MK | Su

QUICK CHANGE CHUCK

SURFACE CONDITIONING KIT

 KIT INCLUDES: IR301 1/4" angle head die grinder in a blow molded plastic case with two coarse and two medium grit 3" 3M Rolco™ surface conditioning pads, two coarse, two medium grit 2" 3M Rolco™ surface conditioning pads and a disc holder

> DESCRIPTION K Surface Conditioning Kit



IR-311A

ASCOT SUPPLY CORPORATION



#### 3/8" SUPER DUTY AIR IMPACT WRENCH

• Titanium hammer case • 280 ft./lb. of torgue will remove even the toughest nuts and bolts • APPLICATIONS: Transmissions, brakes, exhaust, body repair and underhood

#### 3/8" SUPER DUTY AIR IMPACT WRENCH

• Tremendous power and longer life • APPLICATIONS: Popular choice of professional mechanics for under car, under hood and bench work • Handle exhaust directs air away from work • TORQUE RANGE: 20-150 ft./lb., 180 max.





# Air Tool Lubricants & Conditioner

#### **BLASTER AIR TOOL CONDITIONER**

• APPLICATIONS: Thoroughly cleans internal pneumatic tool parts, restoring them to peak performance and prolonging tool life Breaks loose deposits that create friction and impede smooth operation • Provides long-lasting lubrication • Protects tools from freezing down to -25°F • 12 cans per case



| ASCOT NO. | MFG. NO. | DESCRIPTION  |
|-----------|----------|--|
| 181-00404 | 16-ATC   | Blaster Air Tool<br>Conditioner – 11 Oz.             |
| 181-01404 | ATC-TS   | Blaster Air Tool<br>Conditioner - 3.5<br>Oz. Aerosol |



#### SUPER RED PNEUMATIC AIR TOOL LUBRICANT

• APPLICATIONS: Dissolves gum & varnish formation • Prevents gum & varnish formation • Ensures smoother starts • Special rust & oxidation inhibitor • Clean and free running • 12 bottles per case



ASCOT NO. 181-00406 0406

MFG. NO. DESCRIPTION Super Red Pneumatic Air Tool Oil, 32 Oz.

#### MARVEL AIR TOOL OIL

• APPLICATIONS: Specially formulated for use in all piston type rotary air tools and in-line air lubricators • Prevents rust formation while providing positive lubrication for smooth starting and longer tool life • Assures maximum performance by dissolving gum and sludge • 6 bottles per case



181-00085 MM085 32 Oz.



### **BLASTER AIR TOOL OIL/LUBE**

 APPLICATIONS: Provides lubrication & prolongs tool life • Improves tool performance • Formulated for use with in-line oilers • 12 cans per case



ASCOT NO. MFG. NO. DESCRIPTION 181-00016 Blaster Air Tool 16-ATL Oil/Lube - 16 Oz.









# Air Tool **Accessories**

### **AIR TOOL**

| LUBRICA   | NTS        |  |           |
|-----------|------------|--|-----------|
| ASCOT NO. | MFG. NO.   | DESCRIPTION  |           |
| 181-10510 | 105-LBK1   | 4 Oz. IR 105 Grease, 4 oz.<br>IR10 Oil & Grease Gun Head |           |
| 181-10540 | 105-4T     | (6) 4 oz. Tubes - IR 105<br>Grease Refills               | 1111      |
| 181-11510 | 115-LBK1   | 4 oz. IR 115 Grease, 4 oz.<br>IR10 Oil & Grease Gun Head | 102       |
| 181-11540 | 115-4T     | (6) 4 oz. Tubes - IR<br>115 Grease Refills               |           |
| 181-12228 | R000A2-228 | Grease Gun   | 181-10510 |
| 328-10001 | 100-1      | 1 lb. Grease for Impact Wrenches                         |           |

#### **AIR TOOL COVERS**

• Vinyl boots also absorb some of the tool vibration and protect air impact ratchets, wrenches and drills from external damage

| IR TOOL NO.           | KIT NO.    | ASCOT TOOL NO. |
|-----------------------|------------|----------------|
| 212                   | 212-Boot   | 176-20232      |
| 211                   | 211-P32    | 176-21132      |
| 231C, 231HA-2         | 231-Boot   | 176-23122      |
| 2235                  | 2235M-Boot | 176-13532      |
| 244A, 244A-2          | 244-Boot   | 176-24432      |
| 261, 261-2, 271       | 261-Boot   | 176-26132      |
| 285B-6, 285BS-6, 285B | 285-Boot   | 176-28532      |
| 259                   | 259-Boot   | 176-25925      |
| 2135QXPA, 2135QXPA-2  | 2135M-Boot | 176-21350      |

#### **RETAINING RINGS**

| IR TOOL NO. | ASCOT TOOL NO. | DESCRIPTION                       |  |
|-------------|----------------|-----------------------------------|--|
| 231-425A    | 175-31425      | Socket Retainer for IR231, 231-2  |  |
| R1A-159     | 175-01590      | Retainer O-Ring for IR 231, 231-2 |  |
| 291-425     | 175-91425      | Socket Retainer for IR-281, 285   |  |
| 291-426     | 175-81426      | Retainer O-Ring for IR-281, 285   |  |
|             |                |                                   |  |

#### MOTOR TUNE-UP KITS

• INCLUDES: the vanes, gaskets and seals for a complete tune-up • 231-TK3 also includes ball bearings

| IR TOOL NO.          | KIT NO.  | ASCOT TOOL NO. |
|----------------------|----------|----------------|
| 212                  | 212-TK2  | 176-10212      |
| 231C, 231HA-2        | 231-TK3  | 176-10221      |
| 235                  | 235-TK3  | 176-12313      |
| 244A, 244A-2         | 244-TK2  | 176-10244      |
| 261, 271             | 261-TK2  | 176-10261      |
| 280 Series           | 280-TK2  | 176-10280      |
| 7803A, 7803RA        | 7803-TK1 | 176-17803      |
| 285B-6               | 285B-TK1 | 176-10285      |
| 2235TiMAX            | 2235-TK1 | 176-22235      |
| 2135QXPA, 2135QXPA-2 | 2135-TK2 | 176-32135      |

#### IMPACT WRENCH ACCESSORIES

| ASCOT NO. | MFG. NO.   | DESCRIPTION  |
|-----------|------------|--|
| 175-23142 | IR 231-425 | IR 1/2" Impact Wrench Retainer Clip                |
| 175-33104 | 231-Boot   | Red Protective Boot for IR 231HA-2 Impact Wrenches |
| 175-82651 | H-082651   | 1" Impact Wrench Retainer Clip O-Ring              |
| 175-83071 | P-08371    | O-Ring for 1/2" Impact Wrench Retainer Clips       |



#### INDUSTRIAL STRENGTH SILICONE LUBRICANT

 Teflon<sup>™</sup> fluoropolymer enhances performance • Longlasting lubrication • Won't accumulate • dust & dirt • QUANTITY: 12 per case

16-SL

328-00016



#### HAMMER MECHANISM **TUNE-UP KIT**

• INCLUDES: the anvil, hammer (or pins) and gaskets for the impact mechanism • 110-TK1 includes only the cam ball, two anvil pins and anvil spring

| IR TOOL NO.       | KIT NO.   | ASCOT<br>TOOL NO. |
|-------------------|-----------|-------------------|
| 231C, 244A        | 231-THK1  | 176-00231         |
| 231-2HA-2, 244A-2 | 231-THK2  | 178-01231         |
| 2235TiMAX         | 2235-THK1 | 178-02235         |
| 2135QXPA-2        | 2135-THK1 | 178-02335         |



178-02135



ASCOT NO. MFG. NO. DESCRIPTION

Blaster Silicone Lubricant – 11 Oz.



BUYER'S GUIDE

# Work Stations

#### TOOL CADDY TIRE TOOL STAND

 Provides easy and fast access to all those tools needed quickly when changing tires such as torque sockets, valve stem pullers, hub cap tools, air impact guns and torque sticks • Reduces installation time • Makes tire changing easier & work stations more organized • Reduces the number of trips for the technician by having all tools needed at their fingertips • WEIGHT: 35 lb.

ASCOT NO. 319-50015 DESCRIPTION Tool Caddy Tire Tool Stand

#### MOBILE WHEEL WORK STATION

MFG. NO.

MTTS

 Features gas-strut assisted boom that supports the weight of those heavy impact wrenches • The suspended impact wrench is capable of rotating to the operator desired position • Features side and rear storage compartments designed to organize sockets, tire irons, lubricants, hoses and various wheel parts • Air wrench is supported and held in desired position • Air wrench suspension boom allows for directional freedom and reduces damage

ASCOT NO. MFG. NO. 515-00555 WS-005 DESCRIPTION Mobile Wheel Work Station

#### TIRE TOOL STATION

• Organize your tools • Universal top tray with slots for torque sockets, etc. • Dual cradles for impact guns, 1/4" airline connections • INCLUDES: (2) 25' x 3/8" recoil hoses with 1/4" swivel fittings

| ASCOT NO. | MFG. NO. | DESCRIPTION       |
|-----------|----------|-------------------|
| 515-02400 | 2400     | Tire Tool Station |



